
INFINITY
Nanjing Infinity Technology Co.,Ltd.

No. 55 Runfa Road,Jiangning District,Nanjing,China
Tel: +86-025-52634026
Phone & WeChat: +86 13851427688 / 15618213281
Email: inf1188@vip.sina.com



Frame Core Chokes SQ0808 Series

Characteristics：

- Compact Size with Low Leakage Flux due to the O-type SQ ferrite core
- Low Stray Capacitance for broad-frequency noise attenuation
- Single-Layer Winding eliminates risk of interlayer shorts
- High Normal Mode Noise Suppression
- Reduced Winding Time by up to 90%
- High Inductance achieved via proprietary ferrite mixing and sintering technology

Common Applications：

- Switching Power Supplies
- LED Drivers
- Industrial Automation
- Communication Devices
- Household Appliances
- Audio/Medical Equipment

Specifications:

- Rated Voltage: AC/DC 250V
- Operating Temperature: -40°C to +120°C
- Withstanding Voltage:
  AC 2000V for 60 sec or
  AC 2400V for 1 – 2 sec (Line-to-Line)
- Insulation Resistance: ≥100 mΩ (DC 500V)
- Temperature Rise: ≤40°C at rated current

Options：

- Bulk or Tape & Reel packaging
- Custom inductance, wire gauge, and winding configuration
- Alternative ferrite materials for tailored performance
- SMD versions available on request

Model Comparison Table


Test Condition:1KHz/0.3V AT(25°C)

Specifications and Electrical Characteristics

INF Code	Inductance	Wire Diameter	Turns	DC Resistance	Applicable Enameled Wire Diameter	Operating Current	Applicable Power
SQ0808-120uH	120uH	0.25*1.0	6	15mΩ MAX	0.6	2.5~3.0A	18~270W

Dimensions:[mm]

V-Type 1



V-Type 2

